

# Nero

— OSSIDO



1620x3240 mm / 63.7"x127.5"



1620x3240 mm      Laminam 5+  
1620x1620 mm      Laminam 5+  
1620x3240 mm ◆    Laminam 5 | Laminam 12+ | Laminam 20+

1000x3000 mm / 47.2"x118.1"

6 Available Faces Supplied Randomly

6 Facce fornite in modo "random" | 6 Disponible en faces fournies aléatoirement |

Dekor mit 6 möglichen Verläufen Musterverlauf nach Zufallsprinzip | 6 Caras disponibles de manera aleatoria.



1000x3000 mm      Laminam 3+ | Laminam 5  
1000x3000 mm ◆    Laminam 3

◆ FULL SIZE

Untrimmed end product. | *Lastra formata "uscita forno" quindi non rifilata.*

*Produit fini non coupe | Plattenformat nicht rektifiziert | Tabla formata "salida de horno" y, por lo tanto, no recortada.*

Pictures colours and features have to be considered indicative. | *Non è le caratteristiche delle immagini sono da considerarsi indicativi.* | Les teintes et les caractéristiques des images sont uniquement à titre indicatif |  
*Die gezeigten Farben und Muster sind zufällig und nicht verbindlich. | Los tonos y las características de las imágenes deben considerarse solamente indicativas.*



## Coefficient of friction: Laminam 5 / Laminam 5+

*Coefficiente d'attrito | Coefficient de frottement | Reibungskoeffizient | Coeficiente de fricción*

Norm-Method		1620x3240 mm
<i>Norma-Metodo   Norme-Méthode  </i>	1000x3000 mm	1620x1620 mm
<i>Norm-Methode   Norma-Metodo</i>		
DIN 51130	R9	R9
DIN 51097	A	N.C
ANSI A137.1 (DCOF)	≥ 0,42*	≥ 0,42*

\* Guaranteed if requested at the time of ordering | *Garantito su richiesta in fase d'ordine* |

*Garanti sur demande au moment de la commande | auf Anfrage in der Bestellphase garantier | Garantizado por encargo durante la fase de pedido*

## Pendulum

### Norm-Method

*Norma-Metodo | Norme-Méthode |*

*Norm-Methode | Norma-Metodo*

Spanish test	UNE-ENV 12633:2003	on demand
English test	BS 7976-2:2002 PENDULUM TEST	on demand
Australian test	AS/NZS 4586	on demand